



## Flanged Bearing with extended inner rings



Bearing Number	Dimensions				Wfs	Basic Load Rating		Limiting Speed (X1000 RPM)		Weight(Kg)		
	d	D	Df	B		Cr(N)	Cor(N)	Grease	Oil			
MF52zz	2.0000mm	5.0000mm	6.2000mm	2.5000mm	0.600mm	144	40	85	100	6	0.8000mm	0.25
F692	2.0000mm	6.0000mm	7.5000mm	2.3000mm	0.600mm	281	79	75	90	6	1.2000mm	0.35
MF52	2.0000mm	5.0000mm	6.2000mm	2.0000mm	0.600mm	144	40	85	100	6	0.8000mm	0.19
F682zz	2.0000mm	5.0000mm	6.1000mm	2.3000mm	0.600mm	144	40	85	100	6	0.8000mm	0.24
F682	2.0000mm	5.0000mm	6.1000mm	1.5000mm	0.500mm	144	40	85	100	6	0.8000mm	0.19
F601xzz	1.5000mm	6.0000mm	7.5000mm	3.0000mm	0.800mm	281	79	75	90	6	1.2000mm	0.5
F601x	1.5000mm	6.0000mm	7.5000mm	2.5000mm	0.600mm	281	79	75	90	6	1.2000mm	0.38
F691xzz	1.5000mm	5.0000mm	6.5000mm	2.6000mm	0.800mm	144	40	85	100	6	1.0000mm	0.33
F691x	1.5000mm	5.0000mm	6.5000mm	2.0000mm	0.600mm	144	40	85	100	6	1.0000mm	0.26
F681xzz	1.5000mm	4.0000mm	5.0000mm	2.0000mm	0.600mm	95	26	100	120	7	0.6000mm	0.17
F681x	1.5000mm	4.0000mm	5.0000mm	1.2000mm	0.400mm	95	26	100	120	7	0.6000mm	0.12
MF41x	1.2000mm	4.0000mm	4.8000mm	1.8000mm	0.400mm	95	26	110	130	7	0.6000mm	0.12
F691	1.0000mm	4.0000mm	5.0000mm	1.6000mm	0.500mm	120	30	100	120	5	0.8000mm	0.14
F681	1.0000mm	3.0000mm	3.8000mm	1.0000mm	0.300mm	82	21	130	150	6	0.6000mm	0.04
F692 2rs	2.0000mm	6.0000mm	7.5000mm	3.0000mm	0.800mm	281	79	75	90	6	1.2000mm	0.35
F692zz	2.0000mm	6.0000mm	7.5000mm	3.0000mm	0.800mm	281	79	75	90	6	1.2000mm	0.45
MF62	2.0000mm	6.0000mm	7.2000mm	2.5000mm	0.600mm	281	79	75	90	6	1.2000mm	0.34
MF62zz	2.0000mm	6.0000mm	7.2000mm	2.5000mm	0.600mm	281	79	75	90	6	1.2000mm	0.45
MF72	2.0000mm	7.0000mm	8.2000mm	2.5000mm	0.600mm	328	103	63	75	7	1.2000mm	0.5
MF72 2rs	2.0000mm	7.0000mm	8.2000mm	3.0000mm	0.600mm	328	103	63	75	7	1.2000mm	0.6
MF72zz	2.0000mm	7.0000mm	8.2000mm	3.0000mm	0.600mm	328	103	63	75	7	1.2000mm	0.6
F602	2.0000mm	7.0000mm	8.5000mm	2.8000mm	0.700mm	328	103	60	71	7	1.2000mm	0.6
F602zz	2.0000mm	7.0000mm	8.5000mm	3.5000mm	0.900mm	328	103	60	71	7	1.2000mm	0.73
F682x	2.5000mm	6.0000mm	7.1000mm	1.8000mm	0.500mm	178	59	71	80	8	0.8000mm	0.24
F682xzz	2.5000mm	6.0000mm	7.1000mm	2.6000mm	0.800mm	178	59	71	80	8	0.8000mm	0.42
F692x	2.5000mm	7.0000mm	8.5000mm	2.5000mm	0.700mm	320	103	63	75	7	1.2000mm	0.5
F692x 2rs	2.5000mm	7.0000mm	8.5000mm	3.5000mm	0.900mm	328	103	63	75	7	1.2000mm	0.68
F692xzz	2.5000mm	7.0000mm	8.5000mm	3.5000mm	0.900mm	328	103	63	75	7	1.2000mm	0.68
MF82x	2.5000mm	8.0000mm	9.2000mm	2.5000mm	0.600mm	180	67	71	80	7	3.9690mm	0.42

## Flanged Bearing with extended inner rings

F602x	2.5000mm	8.0000mm	9.5000mm	2.8000mm	0.700mm	469	142	60	71	6	1.5880mm	0.72
-------	----------	----------	----------	----------	---------	-----	-----	----	----	---	----------	------